

Midland Steel Structures Ltd, Coventry

Permit No: PPC/063

Metal Coatings

Solvent Management Plan 2009 usage

1. Objective

To establish a Solvent Management Plan following the Secretary of State's Guidance for Coating of Metal and Plastic Processes PG6/23 (04). This document particularly refers to the requirements of paragraph 5.12.

2. Definitions and Interpretations

The Guidance Note refers to specific Inputs and Outputs of organic solvent. The interpretation of the definitions in relation to Midland Steel Structures Ltd is as follows;

Definition Ref	Interpretation
I ₁ Purchased input	The input quantity of VOC will be the sum of all coatings and thinners used in the application process and solvent used for cleaning purposes
I ₂ Recycled & reused	Organic solvents recovered and reused as solvent input into the process. This is not applicable to MSS.
O ₁ Waste gasses	The emission of VOC from the exhaust stacks in the spray booths. This is calculated as the difference between the input VOC and the other output VOC.
O ₂ Lost in water	MSS do not use a process where solvents are washed in water and therefore this output requirement is not applicable
O ₃ Residual	It is believed that no organic solvent remains as residue in the product and therefore this output requirement is not applicable
O ₄ Uncaptured emissions	<p>All mixing of the coating components, transfer of coatings and cleaning of application equipment is carried out in extracted areas. This output requirement is therefore not applicable.</p> <p>The work method employed at MSS involves the sprayed work pieces remaining in the spraying area, with the extraction turned on, until they are dry. As there is no forced air make-up into the building, then air for the spray booth extraction is drawn from outside the building through any holes e.g. doors, available. Due to the size of the booths this is a high air volume. In this situation air movement is always into the building which prevents fugitive emissions through doors etc.</p>
O ₅ Chemical/Physical reactions	None of the coatings used at MSS generate emissions from chemical or physical reactions and therefore this output is not applicable.
O ₆ Collected waste	Organic solvents contained in collected waste arise from the residue of coating materials left in the drums and from waste cleaning solvents. The drums are partially vented prior to collection.
O ₇ Sold on	A proportion of coatings bought are subsequently sold on to sub-contractors.

O ₈ Recovery for resale	The waste resulting from the gun cleaning process contains 27% VOC and is not considered suitable for recovery.
O ₉ Others	<p>To the best of our knowledge all solvent releases are accounted for in the above definitions and therefore this output is not applicable.</p> <p>The waste on the floors of the spray booth is a result of the overspray from the spraying process. A significant part of the solvent in the paint is lost during the transfer of paint from the spray gun to workpiece and the overspray paint reaching the floor is relatively dry. Any remaining solvent is removed by the air flow into the extraction system and subsequently vented through the ducts. The solid waste is subsequently removed as dry dust.</p>

3. Methodology

Inputs

3.1 Input I₁

The input data for materials used in the process is calculated from information supplied by the materials manufacturers.

Outputs

The known outputs cannot realistically be calculated with this level of accuracy and traceability. In order to estimate the relevant outputs the following methodologies have been used.

3.2 Output O₆ - Organic solvents contained in collected waste.

3.2.1 From the residue of coating materials left in nominally empty drums.

This output is calculated from an estimated 5mm thick residual layer in a coatings container after emptying into a mixing drum or being pumped to the spray gun.

The coating VOC content used to determine O₆ is a weighted figure calculated from the total VOC weight of all materials in kg divided by the total usage of all materials in litres less gun cleaner. (It is not an average VOC content of the materials used)

The volume of material in a drum varies with the type of material. For a typical drum the depth of material would be 500mm. The residue therefore is equivalent to 1% of the drum height and therefore 1% volume of coating in the drum. The calculated average coating VOC content can be used to determine the VOC content of the residue then extrapolated to give a total. The average coating VOC content of the residue is 0.363 kg/litre. The residual volume of coatings is 1% total litres less gun cleaner or 220.11 litres. The total VOC content of the residue left in nominally empty drums is therefore 80.0 kg or 0.080 tonnes.

3.2.2 Gun cleaner residue

Gun cleaner solvent residue is collected every 21 weeks in a 205 litre drum or 2.5 drums per year. The VOC content of this residue has been measured as 0.278 kg/litre. This gives an equivalent annual VOC waste from this stream of 147.8 kg or 0.148 tonnes.

3.3 Output O_7 - Organic solvents, or organic solvents contained in preparations, which are sold or are intended to be sold as a commercially valuable product.

This output, for materials sold on to sub-contractors, is calculated using the data used for I_1 .

4. Determination of Annual Solvent Consumption

The VOC content and solids content are available from data supplied by the coating manufacturer. The VOC or solids content of the total coating used can be determined by multiplying the volume by VOC or solids content as appropriate.

The annual actual consumption of organic solvents (C) is

$$C = I_1 - O_8$$

5. Determination of Target Emission

For installations with a solvent consumption of 5-15 tonnes the Target Emission is

Total Mass of Solids (para 5.6 (a) PG6/23(04)) x 0.60 (see Table 6 PG6/23(04))

Compliance with Reduction Scheme is achieved if the annual actual solvent emission determined by the Solvent Management Plan is less than or equal to the Target Emission.

6. Determination of Annual Actual Solvent Emission

The annual actual solvent emission (para 5.7 PG6/23(04)) equals

$$I_1 - O_8 - O_7 - O_6$$

7. Solvent Management Plan

Using the definitions in paragraph 5.12 the input of VOC is

$$I_1$$

The outputs are

$$O_1 + O_6 + O_7 \text{ (other outputs equal zero)}$$

where

I_1 = the quantity of organic solvents used in preparations and as thinners

O_1 = the quantity of organic solvent in exhaust air from the spray booths

O_6 = organic solvents contained in collected empty drums and waste gun cleaner

O_7 = organic solvents contained in coatings sold to sub-contractors

For Midland Steel Structures Ltd during the 12 month period 01/01/09- 31/12/09
(see VOC return in Appendix)

$I_1 = 9.015$ tonnes

$O_1 = 8.787$ tonnes

$O_6 = 0.080$ tonnes (empty drums) + 0.148 tonnes (gun cleaner) = 0.228 tonnes

$O_7 = 0$ tonnes

The annual actual consumption of organic solvents is

$$C = 9.015 \text{ tonnes}$$

The annual actual solvent emission for MSS is

$$9.015 - 0.228 = 8.787 \text{ tonnes}$$

The Total Mass of Solids is shown in the annual VOC return for MSS Ltd. and is

$$25.492 \text{ tonnes}$$

The target emission for 2008 is therefore

$$25.492 \times 0.60 = 15.295 \text{ tonnes}$$

The annual actual solvent emission is therefore less than the target emission.

Appendix-
VOC return 01/01/2009 to 31/12/2009

Midland Steel Structures Ltd, Coventry
Permit No: PPC/063
Metal Coatings
01/01/2009 to 31/12/2009

Total VOC Input (I1)/ tonnes	9.015
Total VOC Output in waste (O6)/tonnes	0.228
Total VOC Output as sold on (O7)/tonnes	0.000
Actual VOC Emission / tonnes	8.787
Total retained solids/ tonnes	25,492
Ratio VOC : solids	0.34 :1

Midland Steel Structures Ltd, Coventry

Permit No: PPC/063

Metal Coatings

01/01/2009 to 31/12/2009

Coatings bought in

Coating	Type	VOC kg/l	solids kg/l	total litres l	total VOC kg	total solids kg
Steelguard 3290	epoxy	0.297	1.303	9840	2922.48	12821.52
Steelguard 3291	epoxy	0.305	1.325	20	6.10	26.50
Amercoat 4116	alkyd	0.421	1.109	11360	4782.56	12598.24
Amercoat 450	alkyd	0.424	0.866	41	15.66	45.84
Gun Cleaner YAP15002	solvent	0.838	0.000	750	628.50	0
Gun Cleaner YAP15008 gun cleaner	solvent	0.851	0.000	775	659.53	0
		Total VOC			9014.83	
		Total solids				25492.1
		Total litres		22786		